



Walco/OMMA OPEN

Water Based Adhesive – “OPEN” Glue Spreader



Walco/OMMA's OPEN model is the “state of the art” glue spreaders / adhesive coater for water based adhesives.

Safety is the priority on this model; the distance between all rollers during cleaning is a minimum of 3” (80mm) for a safe operation. Wired hand controls allow step rollers rotation.

An independent motor is installed on each roller, for a total of two (2) drive assemblies, granting perfect spreading quality, greater application precision, and a vibration free application with an extremely solid and sturdy structure.

This glue spreader / adhesive coater includes all best technical features and can be easily equipped with upgrades such as automatic roller cleaning, automatic glue dosing, thickness servo-positioning, automatic line extraction, remote servicing, and many, many additional key features.

Additionally, the OPEN can be equipped with communication devices for an easy integration on high-performance projects and accessories to support the operator.

Dosing and spreading rolls are rubber covered; spreading roll finishing can be smooth or with grooves that may be configured in accordance with your needs.

Standard equipment includes a double motorized out feed panel shaft with discs to help extraction of short panels, different components in stainless, and pressure free glue sealing plate.

The OPEN can be equipped with [MIXER](#) (automatic device to feed multi-component glues) or with an automatic mono component glue feeder [MGF](#). It can be also cooled with a glue feeding conditioning device [CRIO](#), with a specific positioning of the rollers.

OPEN working widths start from 50” to 86” (1.400 to 2.200mm) up to 0.14 “(3.600mm).

The OPEN can be configured for different types of glues: polyurethane, melaminic, phenolic.

For more information about Walco/OMMA's OPEN contact sales@walcomachine.com.